



**LED LIGHTING SOLUTIONS**

*Precision Lighting for Naval Defense Platforms*



## ***SSL-560 Globe Low Voltage***

### **Product Features**

- Power: 20-30VDC
- 0-10v Dimming
- 5-25 Watts
- White, Blue, Amber and Red
- 100,000 Hours
- Under 5 lbs (Cord not included)
- High Impact Heat-Resistant Tempered Glass
- Die Cast Aluminum Body, SS Hardware
- 3-10' Military Grade Cord Available
- Powder Coated, Anti-Corrosion
- 4 Hole Aluminum Bracket (Legacy Hole Patterns)
- MIL-DTL16377 Compliant



## Ordering Part Number

# SSL-560VDC

<b>92.2</b>	<b>0</b>
SM White Globe	No Cable
<b>93.2</b>	<b>3</b>
SM Red Globe	3' LSTHOF-3 Cable
<b>93.4</b>	<b>6</b>
SM Blue Globe	6' LSTHOF-3 Cable
<b>93.5</b>	<b>10</b>
SM Amber Globe	10' LSTHOF-3 Cable
<b>112</b>	<b>DM</b>
LG White Globe	0-10V Dimming
<b>113</b>	
LG Red Globe	
<b>113.1</b>	
LG Yellow Globe	

## Configuration Example

Part No.      SSL-560VDC-92.2-3

Description LED Globe, 24VDC, 4100K (White), 3' LSTHOF-3 Cable

- Colored LED's operate at 5 Watts
- White LED's operate at 25 Watts
- Large Globe comes with Bracket, see diagram below
- Small Globe does not come with Bracket or Hardware.

## Dimensions



M16377/26 OPTION  
5LBS 9OZ



M16377/27 OPTION  
4LBS 2OZ

