



LED LIGHTING SOLUTIONS

Precision Lighting for Naval Defense Platforms



SSL-220 HP Flood Low Voltage

Product Features

- Power: 120/250VDC (10K Surge Protector)
- 81, 124, 175, 234, 346 484 Watts
- IP66/67
- UL1598/A, UL844 Class 1, Div 2 (A,B,C,D)
- Temp -40C - +65C
- 5000K (Amber Color Optional)
- 150,000 Hours (L70)
- 28lbs (Single Head) - 50lbs (Dual Head)
- A360 Die Cast Aluminum Construction
- Dimmable Driver (0-10V)
- 10K Surge Protection
- 2 3/4" Input Cable Entry
- Beam Pattern: NEMA 4, 6, 7x6, Asymmetric, Asymmetric Wide
- ABS
- MIL-DTL-16377 Compliant



©LEDLIGHTINGSOLUTIONS DIRECT.Info@1LLS.com OFFICE.855.309.1702 FAX.941.296.7313
WWW.LEDLIGHTINGSOLUTIONS.COM

All rights reserved. LED Lighting Solutions reserves the right to change specifications for product improvement without prior notice

Ordering Part Number

SSL-220VDC

81	50	4	YMS	ND	NV
13,200 Lumens	5000K	60 Deg. Med	Yolk Mount Straight	Non-Dimming	No Visor
124	40	6	YMA	DM	VS
19,100 Lumens	40000K	120 Deg. Wide	Yolk Mount Angle	Dimming Driver	Visor
175	27	7	SF		
25,000 Lumens	2700K	130 Deg. Very Wide	Slipfitter 1-1/4 - 2 3/8 OD		
234					
31,600 Lumens					
346					
51,000 Lumens					
484					
65,000 Lumens					

Configuration Example

Part No. SSL-220VDC-124-50-4-YMS-ND-VS

Description LED High Powered Flood, 120/250VDC, 124 Watts, 5000K, 60 Deg. Beam, Yolk Mount Straight, Non-Dimming, Visor

Dimensions

