



LED LIGHTING SOLUTIONS

Precision Lighting for Naval Defense Platforms



MILX9 High Bay Low Voltage

M16377/13 - Symbol 74 Equivalent

Product Features

- Power: 20-30VDC
- 0-10V Dimming
- 90 Watts (4100K)
- 20 Watts (Colored)
- White, Red, NVD Options
- 26 lbs
- 100,000 Life Hours
- Die-Cast Aluminum Body
- Polycarbonate Lens
- Stainless Steel Hardware
- Three Shock Mounts
- 3/4" Cord Grip
- Input Port within each head
- MIL-DTL-16377 Compliant
- ABS



©LEDLIGHTINGSOLUTIONS DIRECT.Info@1LLS.com OFFICE.855.309.1702 FAX.941.296.7313
WWW.LEDLIGHTINGSOLUTIONS.COM

All rights reserved. LED Lighting Solutions reserves the right to change specifications for product improvement without prior notice

Ordering Part Number

LLS360-MILX9VDC

40- SD-

8
Medium Lens
F
Flat Lens

EM
Emergency
EMRW
Emergency Red
EMCW
Emergency Cyan

0
No Cable
LST10
10' LSTHOF-3 Cable
LST15
15' LSTHOF-3 Cable
LSH10
10' LSFHOF-3 Cable
LSF10
15' LSFHOF-10'
7XW3
EM Cable
DM
0-10V Dimming

EM units will be provided with 7XW-3 Cable.

*EM units will be provided with 7XW-3 Cable.

Configuration Example

Part No. LLS360-MILX9VDC-8-40-SD

Description : LED MILX9, 20-30VDC, Medium Lens, 4100K, Standard Mount, Non-EM, No Cable

Medium Lens Shown Below

