



LED LIGHTING SOLUTIONS

Revolutionary Concepts For Shipboard Lighting

LLS MILX-WLS Floodlight Luminaire



Model No. **LLS-MILX-WLS**

Product Features

- 120/277VAC 50/60Hz
- Power Options: 50 or 100Watts (300W, Par56 Equivalent)
- IP66
- Working Temperature: -20~+60 C
- 4000K
- 100,000 Hours
- Weight: 11.25lbs
- Die-Cast Aluminum- Stainless Steel Hardware and Mount
- Marine Grade, PC5M Anti-Corrosion White Finish
- MIL-DTL-16377 Compliant
- Mounts to a 1-7/8" OD Pipe (Mount not shown)
- Cord and Plug Optional





LED LIGHTING SOLUTIONS

Revolutionary Concepts For Shipboard Lighting

Ordering Part Number:

LLS-MILX-WLS-	Wattage	Color	Beam	
	50	WT	NB	CP (Cable and Plug)
	100	RR	WB	CA (Cable Only)
		CY		

CONFIGURATION EXAMPLE

Part No. LLS-MILX-WLS-50-WT-WB-CP

Description LLS LED Flood, White (5000K), Wide Beam, Cable and Plug

4000K or 5000K is available. Please specify when ordering.

LLS-MILX-WLS Dimensions

