



# LED LIGHTING SOLUTIONS

Revolutionary Concepts For Shipboard Lighting

## LLS MILX-WLS Floodlight Luminaire



### Model No. **LLS-MILX-WLS**

#### Product Features

- 120/277VAC 50/60Hz
- Power Options: 50Watts (300W, Par56 Equivalent)
- IP66
- Working Temperature: -20~+60 C
- 4000K
- 100,000 Hours
- Weight: 11.25lbs
- Die-Cast Aluminum- Stainless Steel Hardware and Mount
- Marine Grade, PC5M Anti-Corrosion White Finish
- MIL-DTL-16377 Compliant
- UL/ABS
- Mounts to a 1-7/8" OD Pipe (Mount not shown)
- Cord and Plug Optional





# LED LIGHTING SOLUTIONS

Revolutionary Concepts For Shipboard Lighting

## Ordering Part Number:

LLS-MILX-WLS-  
Color                      Beam  
\_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_  
WT                      NB                      CP (Cable and Plug)  
RR                      WB                      CA (Cable Only)  
CY

## CONFIGURATION EXAMPLE

**Part No.**                      LLS-MILX-WLS-WT-WB-CP  
**Description**                      LLS LED Flood, White (4000K), Wide Beam, Cable and Plug

## LLS-MILX-WLS Dimensions

